

Tachometers

★★★★★ DIGI PLUS-LINE® Electr. Digital Hand Tachometer

- with LCD display for optical or mechanical speed detection
- measurement accuracy is $\pm 0.02\%$ from the end value ± 1 digit
- 5 digit LCD display, sturdy ABS plastic housing
- direct and non-contact recording of rotation
- automatic Off-function, after 30 sec.
- automatic Min/Max/Average memory-function, recall by memory button
- mode function for different measurement units
- extensive accessories is included: Hand Tachometer, 10 reflective tags, adaptor for direct measuring 1:1, rubber tip, track wheel 0.1 m and 6"
- incl. 2x 1.5 V battery (type AA, art.-no. 609282)
- operation manual and test certificate, in sturdy carrying case


Option

- art.-no. 270160/8 set of reflective tags (10 pcs.)



ART^{NO} 270160



ART ^{NO}	 1 / min.	measuring distance max. mm	storage temperature °C	operation temperature °C	KG	ART ^{NO} CC
270160	1 - 99999	600 (optically)	-20° ~ +70 °	0° ~ +50 °	0.250	2794110

★★★★★ DIGI PLUS-LINE® Electr. Digital Hand Tachometer

- especially for maintenance and service tasks for lifts
- special set for lift and wire/cable measurement
- with LCD display for optical or mechanical speed detection

- measurement accuracy is $\pm 0.02\%$ from the end value ± 1 digit
- 5 digit LCD display, sturdy ABS plastic housing
- direct and non-contact recording of rotation
- automatic Off-function, after 30 sec.
- automatic Min/Max/Average memory-function, recall by memory button
- mode function for different measurement units
- extensive accessories is included: Hand Tachometer, 10 reflective tags, adaptor for direct measuring 1:1, rubber tip, track wheel 0.1 m and 6", adapter for lift-, textile yarn- and wire measuring
- incl. 2x 1.5 V battery (type AA, art.-no. 609282)
- operation manual and sturdy carrying case


Option

- art.-no. 270160/8 set of reflective tags (10 pcs.)



ART^{NO} 270161



ART ^{NO}	 1 / min.	measuring distance max. mm	storage temperature °C	operation temperature °C	KG	ART ^{NO} CC
270161	1 - 99999	600 (optically)	-20° ~ +70 °	0° ~ +50 °	0.250	2794110

Accessories for Electr. Digital Handtachometers



ART No 270160/1



ART No 270160/2



ART No 270160/3



ART No 270160/4



ART No 270160/5



ART No 270160/6



ART No 270160/7



ART No 270160/8



ART No 609282

In each set contain:

set content										
270160	-	✓	✓	✓	✓	✓	✓	✓	✓	✓
270161	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

ART No	product description
270160/1	adapter
270160/2	extension shaft
270160/3	change attachment
270160/4	drive cone

ART No	product description
270160/5	drive tip
270160/6	measuring wheel 0.1 m
270160/7	measuring wheel 6"
270160/8	set of reflective tags, 10 pcs.



Electr. Digital Stroboscope • IP65

- water-, coolant proof and shock resistant hand-held device
- e.g. for use in the automotive industry and mechanical engineering
- for measuring the speed of high-speed turns
- in a rugged aluminium- / ABS plastic-housing
- with modern LED technology, precise working electronic
- for non-contact measurements

- large LCD display, multiple lines
- with adjustable flash duration, light emission 1500 lux @ 6000 FPM / 20 cm
- no waste of flash tubes
- resolution ± 0.1 (30 ~ 999 FPM) / ± 1 (1000~300000 FPM); FPM=flashes/min.
- operation temperature 0° C ~ +45° C
- incl. 3x 1.5 V battery (type AA, art.-no.: 609282), operation time max. 10 hrs.
- in sturdy carrying case, with operation manual



ART No			flash colour		
610101	30 ~ 300000	0.02% (± 1 Digit)	white 6500 K	195 x 95 x 50	0.400